



ARISA | 630T PRESS

Straightside Press
Model S-2-630-350-150-LDE

Features:

- Hydraulic overload safety device
- Pneumatic clutch and brake
- LINK-DRIVE transmission
- Variable speed
- Lubrication control
- Die space lighting
- CE standard - UL Norm
- Light curtains - front & rear
- Die protection - 8 point
- Anti-vibration devices
- Tonnage monitor - 4 channel
- Motorized bed plate - front of press

Availability: 4 months from order date

SPECIFICATIONS	METRIC	U.S.
Force	6.300 KN (630 TON)	693 TON
Force Point - Distance off Bottom	7 mm	.28 in
Variable Speed	12-60 spm	12-60 spm
Main Motor Power	110 KW	147 HP
Fixed Stroke	300 mm	11.8 in
Shut Height	800 mm	31.5 in
Height Adjustment	250 mm	9.8 in
Slide Dimensions (LR x FB)	3.500 x 1.500 mm	137.8 x 59.0 in
Table Dimensions (LR x FB)	3.500 x 1.500 mm	137.8 x 59.0 in
Hole Dimensions in the bed plate (LR x FB)	2720 x 410	107.0 x 16.1 in
Bolster Height	230	9.1 in
Width Between Uprights (F - B)	1.300 mm	51.2 in
Approx. Total Weight	150.000 kg	330,700 lbs.
Approx. Total Height	6,5 m	21.3 ft



Moving bed plate to the front



Link drive transmission
Pneumatic clutch - brake



+1 (419) 628-2331 | sales@nidecpa.com

www.nidecpa.com