



SPECIFICATIONS	METRIC	ENGLISH
Capacity in tons	200	220
Rating point above BDC	5 mm	.196 in
Working energy at 30 SPM	1300 kgf/m	52 in-tons
Stroke Length	203 mm	8 in
Speed Range (SPM)	30-60	30-60
Maximum die height over bolster (SDAU)	480 mm	18.89 in
Slide adjustment	150 mm	5.90 in
Bolster Area (L-R x F-B)	2400 x 1200 mm	94.48 x 47.24 in
Slide Area (L-R x F-B)	2400 x 1200 mm	94.48 x 47.24 in
Side Window Opening (F-B)	700 mm	27.55 in
Main Motor	22 kW	39.7 hp
Bed & Slide deflection	1/8,000 mm	.0015 in/ft

mmc | SX2-2000

Competitively Priced. Immediate Delivery.

This press is currently under power and available for demonstration at our facility in Minster, Ohio. Can be shipped in one piece to save on rigging and installation charges (no pit required). Start up assistance on your floor and a full one (1) year parts and labor warranty included.

Also features:

- Welded steel frame with pre-stressed tie rod construction
- Box-type slide with eight (8) point guiding
- Automatic recirculating lubrication
- Single geared center drive
- Hydraulic overload protection
- Wet-type clutch and brake
- Yaskawa VFD
- Leveling mounts included
- Console-type control with Mitsubishi PLC
- Color touchscreen features: 100 job storage capability, 8 die protection inputs, 8 PLS outputs

