



SPECIFICATIONS	METRIC	ENGLISH
Capacity in tons	45	49.5
Rating point above BDC	3.2 mm	.13 in
Stroke Length	80 mm	3.15 in
Speed Range (SPM)	40-100	40-100
Maximum die height over bolster (SDAU)	250 mm	9.84 in
Slide adjustment	60 mm	2.36 in
Bolster Area (L-R x F-B)	850 x 440 mm	33.46 x 17.32 in
Slide Area (L-R x F-B)	400 x 300 mm	15.75 x 11.81 in
Throat Depth	225 mm	8.86 in
Main Motor	3.5 kW	5 hp
Bed & Slide deflection	1/6,000 mm	.002 in/ft

MMC | CX1-450

Competitively Priced. Immediate Delivery.

Need a 45-ton gap press in a hurry? Located at the Minster, Ohio facility, this press is specially priced and ready for immediate delivery.

Also features:

- Welded steel frame
- Cast slide with six (6) point guiding
- Automatic grease lubrication
- Single geared drive
- Hydraulic overload protection
- Wet-type clutch and brake
- Yaskawa VFD
- Leveling mounts included
- Wintriss WPC 2000 clutch and brake control
- Stock number 0C0052

Start-up assistance on your floor and a full one (1) year parts and labor warranty are included!

