



New Greenerd 4D-50-30 x 24-30R12 Hydraulic Press

New 2017
NPA Stock #200149P



Photo of actual machine

Press Specifications:

- 10- 50 0 U.S. Tons Capacity (89 - 445 kN)
- 18.00 in. Stroke Maximum, Adjustable (457 mm)
- 24.00 in. Daylight (610 mm)
- 6.00 in. Shut height (152 mm) (DL – Max. Stroke)
- 30.00 x 24.00 in. Work Area (762 mm x 610 mm)
- 54.00 x 110.00 in. Overall Dim's (1372 mm x 2794 mm)
- 4.00 in. Column Diameter (102 mm)
- 5.00 in. Ram Diameter (127 mm)
- 7.00 in. Cylinder Diameter (178 mm)
- 36.00 in. Bed to Floor Height (914 mm)
- Ram Speed:
 - 494 IPM, closing
 - 72 IPM, closing
 - 515 IPM, opening
- 20 HP, 1800 RPM Drive Motor (14.9 kW)
- 30 GPM & 12 GPM pumps (114 & 45 L/PM)
- 105 gallons reservoir capacity (398 liters)
- 2,598 PSI Maximum System Pressure (17,913 kPa)
- 230 VAC, 60 hz, 3 ph incoming power

Press Specifications (cont'd):

- 2 – 10 tons Adjustable Cushion (8 – 89 kN)
 - 2 Tons Maximum Ejection Force (8 kN)
 - 6.00 in. stroke, adjustable (152 mm)
 - 4.00 in. cylinder bore (102 mm)
 - 2.50 in. ram diameter (64 mm)
 - 8.00 L-R x 12.00 in R-L Platen (203 x 305 mm)
 - 2410 PSI Maximum System Pressure (16,616 kPa)

Features:

- Distance Reversal
- Pressure Reversal
- Pre-slow Down Circuit
- Water-cooled Heat Exchanger
- Dwell Timer

Note: All specifications contained herein are as the machine was originally manufactured and are subject to change at time of inspection.

Price, Ex Works, Endicott, NY: Price On Request

Contact:

Richard S. Ruck, Used Equipment Manager
567-644-5037 • richard.ruck@nidecpa.com

Nidec Press & Automation

240 West Fifth Street
Minster, OH 45865
419-628-2331 • www.nidecpa.com