



PRESS & AUTOMATION

USED MACHINERY



Used Minster E2-600-120 Straight Side Press w/Feed Line

New 1998

NPA Stock # 100330P – s/n 29460



Photo of actual machine

Press Specifications:

- 600 U.S. Tons Capacity @ ½" (5338 kN @ 13 mm)
- 14.00 in. Stroke (356 mm)
- 6.00 in. Slide Adjustment (152 mm)
- 37.00 in. Shutheight, SDAU, on Bed (940 mm)
- 120.00 x 60.00 in. Slide Area (3048 x 1524 mm)
- 120.00 x 60.00 in. Bed Area (3048 x 1524 mm)
- 114.00 x 26.00 Bed Opening (2896 x 660 mm)
- 122.00 in. Between Gibs (3099 mm)
- 53.00 in. Upright Opening (1346 mm)
- 28.00 in. Floor to top of Bed, w/pit (711 mm)
- 0 – 60 SPM
- 100 HP, 1800 RPM Drive Motor (75 kW)
- 480VAC/60Hz/3ph Incoming Voltage
- 215,000 lbs. Approximate Weight, Press Only

Equipped With:

- Single Geared
- Minster Hydraulic Clutch & Brake
- Hydraulic Tie Rod Nuts
- Flywheel Brake, electrically interlocked
- Pneumatic Counterbalance
- Long Barrel Motorized Slide Adjustment
- Minster Monitorflow Recirculating Lube System
- Minster Centralized Press Control
 - Sliding Pendant
- Minster Production Management Control
 - 10.4 in. Color Touch Screen
 - 16 Pole PLS for press and feed setup
 - 50 Tool Storage Capacity
 - Production Counters
 - Maintenance Reminders
 - PMC 16 Point Die Protection
 - PMC Single Stroke Control
- Eddy Current Drive

Price, As Is Where Is: Price On Request

Note: All specifications contained herein are as the machine was originally manufactured and are subject to change at time of inspection.

Contact:

Richard S. Ruck, Used Equipment Manager
567-644-5037 • richard.ruck@nidecpa.com

Nidec Press & Automation

240 West Fifth Street
Minster, OH 45865
419-628-2331 • www.nidecpa.com



Feed Line for Minster E2-600-120 Straight Side Press

Minster MEF7-50 Electric Feed



Photo of similar machine

- 50.00 in. Max Material Width (1270 mm)
- 0.030 in. Min Material Thickness (0.76 mm)
- 0.312 in. Max Material Thickness (8 mm)
- 24.00 in. Max Mat'l Width @ Max Thickness (610 mm)
- Motorized Pass Line Adj., Pass Line Mtg. Clamps
- End of Stock Sensor
- Chrome Blast Feed Rolls
- **MTT15-50D Hydraulic Threading Table**

Minster MR30-50S Single Stock Reel



Photo of Similar Machine

- 30,000 lb. Maximum Coil Weight (13,500 kg)
- 50.00 in. Maximum Coil Width (1270 mm)
- 20.00 – 24.00 in. I.D. Expansion Range (508 – 610 mm)
- 72.00 in. Maximum Coil O.D. (1829 mm)
- Hydraulic Expansion & Jog Drive
- Pneumatic Drag Brake
- Spring Set/Hydraulic Release Holding Brake

Minster MSH-30-50-7 Stock Straightener



Photo of similar machine

- 50.00 in. Max Material Width (1270 mm)
- 0.020 in. Min Material Thickness (0.5 mm)
- 0.110 in. Max Mat'l Thickness @ Full Width (2.8 mm)
- Manual Work Roll Adjustment
- Peeler Table
- End of Stock Sensor
- Driven Hold Down Arm w/End Flattener

Minster MCCH-35 Coil Car



Photo of similar machine

- 35,000 lb. Max Coil Weight (15,750 kg)
- 72.00 in. Maximum Coil Width (1829 mm)
- 72.00 in. Maximum Coil OD (1829 mm)
- 42.00 in. Minimum Coil OD (1067 mm)
- 18.00 in. Maximum Lift (458 mm)