



PRESS & AUTOMATION

USED MACHINERY



Used Minster E2-400-120 Straight Side Press

New 1996

NPA Stock #100331P – s/n 29084



Photos of actual machine

Press Specifications:

- 400 U.S. Tons Capacity (3559 kN)
- 12.00 in. Stroke (305 mm)
- 6.00 in. Slide Adjustment (152 mm)
- 34.00 in. Shutheight, SDAU, on Bed (864 mm)
- 6.00 in Bolster Plate Thickness (152 mm)
- 120.00 x 54.00 in. Slide Area (3048 mm x 1372 mm)
- 120.00 x 54.00 in. Bed Area (3048 mm x 1372 mm)
- 114.00 x 25.00 in. Bed Opening (2896 mm x 635 mm)
- 122.00 in. Between Gibs (3099 mm)
- 31.00 in. Upright Opening (787 mm)
- 27.00 in. Floor to Top of Bed, with mounts (686 mm)
 - Requires 20" deep pit
- 0 - 80 SPM
- 75 HP/1800 RPM Drive Motor
- 480 VAC/60 hz/3 ph incoming voltage
- 170,000 lbs. Approx. Weight, Press Only (77,111 kg)

Equipped With:

- Single Geared, Extension on both sides
- Minster Hydraulic Clutch & Brake
- Recirculating Lubrication System
- Long Barrel Motorized Shutheight Adjustment
- Eddy Current Drive
- Minster Centralized Motor/Clutch Control
- Sliding Pendant on front of press
- OmniLink 5000 Press Control
 - 8 Channel PLS
 - Programmable for 105 setups
 - Stroke position/press speed indicator
 - Stroke, batch, parts, & quality counters
 - Automatic Top Stop (limited to 180° Stop Angle)
- OmniLink 5000 Die Protection Module, 16 inputs
- OmniLink 5000 4 Channel Tonnage Monitor

Note: All specifications contained herein are as the machine was originally manufactured and are subject to change at time of inspection.

Price, FCA Shipping Point:Price On Request

Contact:

Richard S. Ruck, Used Equipment Manager
567-644-5037 • richard.ruck@nidecpa.com

Nidec Press & Automation

240 West Fifth Street
Minster, OH 45865
419-628-2331 • www.nidecpa.com