



Used Minster TR2-30-30 "Pulsar" Straight Side Press

New 1984

NPA Stock # 100340P - s/n 25755



Photos of similar machine

Press Specifications:

- 30 U.S. Tons Capacity @ 0.040 in. (267 kN @1 mm)
- 0.50 in. Stroke (13 mm)
- 1.75 in. Shutheight Adjustment (45 mm)
- 7.25 in. min/9.00 in. max, Shutheight, on bolster, SDAU (184/229 mm)
- 4.38 in. Thick Bolster Plate (111 mm)
- 30.0 in. x 12.0 in. Slide Area (760 mm x 305 mm)
- 30.0 in. x 21.0 in. Bolster Area (762 mm x 630 mm)
- 26.0 in. x 4.0 in. Bolster Opening (660 mm x 102 mm)
- 18.25 in. clearance below bed for parts removal (464 mm)
- 14.0 in. x 5.0 in. Opening thru Quick Access Casting (336 mm x 127 mm)
- 15.5 in. Upright Opening (394 mm)
- 50.00 in. Distance Floor to top of Bolster (1270 mm)
- 100 – 1500 SPM Speed Range
- 25 HP (18.64 kW), 1800 RPM Drive Motor
- 480VAC/60Hz/3ph Incoming Voltage
- 18,800 lb. actual weight, press only (8528 kg)
- 127.5 in Overall Height, floor to top (3239 mm)

Equipped With:

- Flywheel Type, Left Hand Drive, Extension on Right
- Combination Hydraulic Clutch & Brake
- Spring actuated Caliper Brake
- Air Operated Flywheel Brake, electrically interlocked
- Counterweighted drive system provides 100% dynamic balance of slide with 100 lb. (45.4 kg) upper die weight. Upper die weight range for dynamic balancer 0 – 200 lbs. (91 kg)
- Minster Quick Die Access feature with ± 1.75 in. adjustment
- Power Shutheight adjustment
- Recirculating Oil System
- Minster Centralized Press Control
- Electric Oil Heater System
- Eddy Current Main Drive Motor

Price Ex Works, Minster, OH: Price On Request

Contact:

Richard S. Ruck, Used Equipment Manager
567-644-5037 • richard.ruck@nidecpa.com

Nidec Press & Automation

240 West Fifth Street
Minster, OH 45865
419-628-2331 • www.nidecpa.com