

## Specifications

		TVX-2000M	TVX-2000W	TVX-3000M	TVX-3000W	TVX-3300-330	TVX-3300-370
Capacity	kN	2000	2000	3300	3000	3300	3300
Stroke Length	mm	25 / 30	25 / 30	25 / 30	25 / 30	30/40	30/40
Speed	SPM	100 - 450	100 - 500	100 - 410	100 - 450	100 - 360/300	100 - 360/250
Force Point	mm	3.2 *1	3.2 *1	3.2 *1	3.2 *1	3.2 *1	3.2 *1
Die Height	mm	440	440	480	440	520-620	520-620
Die Height Adjustment	mm	60	60	60	60	60	60
Slide	mm	1700 × 650	2000 × 800	2300 × 800	2700 × 1000	3300 × 900	3700 × 1000
Bolster	mm	1700 × 950	2000 × 1000	2300 × 1000	2700 × 1000	3300 × 1000	3700 × 1200
Bolster Thickness	mm	240	240	240	240	240	240
Bed Opening	mm	1400 × 350	1700 × 350	2000 × 400	2400 × 400	3000 × 500	3200 × 500
Bolster Opening	mm	1400 × 300	1700 × 300	2000 × 380	2400 × 350	3000 × 450	3200 × 450
Main Motor	kW	45	55	55	55	55	55
JIS Static Accuracy		Special Grade	Special Grade	Special Grade	Special Grade	Special Grade	Special Grade
Upper Die Weight	kg	Max. 1200	Max. 1300	Max.1500	Max. 2000	Max. 3200	Max. 4000
Gross Weight	kg	48000	50000	75000	65000	130000	140000

\*1 1.6mm above 300SPM