

SPECIFICATIONS

		ANEX-15H	ANEX-30II	ANEX-40II	ANEX-40II W
Tons Capacity	kN	150	300	400	400
Stroke Length	mm	10	20/25/32	20/25/30/32	20/25/32/40
Strokes Per Minute	SPM	200-1800 (2000)	200-1200/1050/900	180-1000/ 900/850/850	180-850/ 800/700/700
Shutheight	mm	220	240	240	240/240/240/235
Shutheight Adjustment	mm	30	40	50	50/50/50/45
Slide Area	mm	500 x 260	600 x 300	750 x 340	950 x 450
Bolster Area	mm	500 x 360	600 x 400	750 x 500	950 x 600
Bolster Thickness	mm	80	90	120	120
Bed Opening	mm	350 x 50	400 x 100	560 x 120	790 x 120
Bolster Opening	mm	250 x 40	350 x 60	500 x 100	700 x 100
Main Motor	kw	15	11	15	18.5

ANEX-60II	ANEX-60II W	ANEX-80II	ANEX-80 W	ANEX-125	ANEX-150
600	600	800	800	1250	1500
20/25/32	25/32/40/45/50	20/25/32/36	25/32	25/36	25/36
100-750/750/650	100-700/ 600/450/400/350	120-700 /600/550/500	120-500/450	100-400/350	100-400/250
300	340/340/335/325/320	320	320	350	350
80	80/80/75/65/60	80	80	80	80
1030 x 500	1280 x 500	1080 x 580	1380 x 580	1480 x 600	1480 x 600
1100 x 600	1350 x 600	1200 x 800	1500 x 800	1600 x 900	1600 x 900
140	140	160	160	180	180
840 x 120	1050 x 120	900 x 160	1200 x 160	1300 x 160	1300 x 160
780 x 80	1000 x 80	860 x 120	1160 x 120	1260 x 120	1260 x 120
22	22	30	30	37	37