

EVX-3300 SERIES SPECIFICATIONS & DIMENSIONS

SPECIFICATIONS	METRIC
Capacity	3,300 kN
Rating off Bottom @ 30 mm Stroke	3.2 mm
FRAME SPECIFICATIONS	
Bed & Slide, R-L	3,700 mm
Bed, F-B	1,200 mm
Slide, F-B	1,000 mm
Shutheight on Bed (SDAU)	990 mm
Bolster Thickness	250 mm
Side Window Opening	580 mm
Weight (kg / lbs)	145,000 kg
STROKE & SPEED SPECIFICATIONS	
Stroke	30, 35, 40 mm
Speed Continuous - @ 30 mm Stroke	450 SPM
Quick Access Slide Travel	80 mm
Slide Adjustment	80 mm
Max Upper Die Weight	5,000 kg
CONTROL SPECIFICATIONS	
Control Platform	APMACS
Motor	75 kW
Energy (@100 SPM)	10 kJ

KEY FEATURES:

- Recirculating oil lubrication
- Electronic tool storage
- Hydraulic quick lift
- Fixed bolster
- 16 pole programmable limit switch
- Automatic counterbalance control
- Electronic shutheight control
- Powered die doors (front & rear)
- Massive cast frame
- Temperature monitoring
- Precision roller guided slide
- Mounting pads - RH and LH end
- Hydraulic clutch and brake
- Automatic shutheight adjustment
- Press isolation mounts

OPTIONAL FEATURES (INCLUDED):

- AIM
- 4 channel tonnage monitor
- 16 point die protection
- Die area lights